RELIABLE, SECURE AND EASY-TO-USE MULTI-FUNCTION PRINTER FOR AN OFFICE OR SME.

The i-SENSYS MF420 series are multi-function printers offering SMEs speed, durability, and quality. Mobile connectivity maximises productivity.







MF426dw

MF428x

MF429x

- Save time with fast print speeds of up to 38ppm
- Increase productivity with double sided single pass scanning
- High quality 1200 x 1200 dpi print resolution
- Easy operation with large colour touch screen
- Improved flexibility with varied media support; A4, A5, A6
- Increase control with the Universal Login Manager (MF428x and MF429x)
- Enhanced security & accounting with uniFLOW (MF428x and MF429x)
- Improve quality & reliability with Canon Genuine all-in-one cartridges
- Application Library allowing automation, added shortcuts and a customised interface
- Secure PIN feature allowing employers and employees maximum control over print jobs



OPTIONAL ACCESSORIES

Cassette Feeding Module - AH1

• Additional 550 sheet paper cassette, 1unit can be added to main unit.

Barcode Print Kit- E1E (Available on MF428x & MF429x)

 Installs bar code fonts for bar code printing. This kit, which is delivered electronically, includes a license access certificate for activation

Send PDF Security Feature Set-E1 (Available on MF428x & MF429x)

• Send encrypted PDF and add digital device signature to PDF files. This kit, which is delivered electronically, includes a license access certificate for activation.

Telephone 6 Kit Long Cord (Available on MF426dw & MF429x)

• Optional telephone handset for fax function.

TECHNICAL SPECIFICATIONS

Machine type Available functions Mono Laser All-In-One

Up to 1200 x 1200 dpi

Approx: 5.5 seconds or less

600 x 600 dpi

Single sided: Up to 38 ppm (A4)

Monochrome laser beam printing

MF421dw / MF428x : Print, Copy and Scan MF426dw / MF429x: Print, Copy, Scan and Fax

Up to 63.1 ppm(A5-Landscape) Double sided : Up to 30.3 ipm (A4)

Modem speed Receive mode Fax resolution 33.6 Kbps (Up to 3 seconds/page⁵) Fax only, Fax/Tel Auto Switch, Answer Mode, Manual

Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi Up to 512 pages⁵

FAX memory Speed dials

Group dials/destinations Sequential broadcast

Max. 310 destinations

Up to 281dials

Memory backup Double sided faxing Permanent fax memory backup (Backup with flash

MEDIA HANDLING

Paper input (Standard)

Paper input (Option)

Scanner type

Yes (Transmit and Receive)

Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only) DRPD, ECM, Auto Redial, Fax Activity Reports, Fax Activity Result Reports, Fax Activity Management Reports

Max. 299 dials / Max. 299 destinations

Print margins

COPIER Copy speed

Toner saver mode

Advanced printing features

First Copy Output Time (FCOT) Copy resolution

Double sided copying

Reduction / Enlargement

PRINTER Print speed

Printing method

Print resolution

Warm-up time

First Print Out Time

Printer languages

Print quality

MF421dw / MF426dw: 45 PCL fonts 136 PostScript fonts MF428x / MF429x: 93 PCL fonts 136 PostScript fonts

Approx. 14 seconds or less from power on

5 mm-top, bottom, left and right 10 mm-top, bottom, left and right (Envelope)

MF421dw: UFRII, PCL 5e¹, PCL6 MF426dw / MF428x / MF429x: UFRII, PCL 5e¹, PCL6, Adobe[®] PostScript

Single sided (A4): Up to 38 ppm Double sided (A4): Up to 30.3 ipm

2-sided to 2-sided (Automatic)

25-400% in 1% increments

Up to 600 x 600 dpi

Up to 999 copies

ADF (A4): Approx. 6.6 seconds or less Platen (A4): Approx. 6.4 seconds or less

Frame Erase, Collate, 2 on 1, 4 on 1, ID card copy

Text, Text/Photo (Default), Text/Photo (High Quality), Photo

Secure Print Print from USB memory key (JPEG/TIFF/PDF) Barcode Print² (MF428x, MF429x only) Google Cloud Print Ready iOS: AirPrint, Canon PRINT Business app Android; Mopria certified, Canon PRINT Business app

Media types

Paper output

Media sizes

Media weights

Platen, 2-sided ADF (single pass)

250-sheet cassette 100-sheet multi-purpose tray 50-sheet ADF 550-sheet cassette

Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Post card, Envelope

Cassette (Standard and optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, GLTR, GLGL, Foolscap, 16K, Custom sizes: Min. 105 x 148 mm Max. 215.9 x 355.6 mm.

Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, GLGL, Foolscap, 16K, Indexcard, Envelope (COMIO, Monarch, C5, DL), Custom sizes: Min 76.2 x 127 mm Max. 215.9 x 355.6 mm.

ADF: A4, A5, A6, B5, Legal, Letter, Statement, Custom sizes: Min. 105 x 128 mm Max 215.9 x 355.6 mm Cassette (standard and optional): 52 to 120 g/m²

multi-purpose tray: 52 to 163 g/m² ADF: 50 to 105 g/m²

A4, Legal, Letter, OFFICIO, B-OFFICIO, M-OFFICIO, GLGL, Foolscap

Custom size - Min. 210 x 279.4 mm Max. 215.9 x 355.6 mm 60 to 120 g/m²

Other features SCANNER

Scan speed

Greyscales

Compatibility

Copy modes

Multiple copy

Colour Scan resolution

Ontical: Up to 600 x 600 dpi Enhanced: Up to 9600 x 9600 dpi

Single sided mono: 38ipm (300x600dpi) Single sided colour: 13ipm (300x600dpi) Double sided mono: 70ipm (300x600dpi) Double sided colour: 26ipm (300x600dpi)

24 bit/24 bit (input/output) Colour scanning depth 256 levels TWAIN, WIA, ICA

TIFF/JPEG/PDF/Compact PDF/Searchable PDF/Encrypted PDF³(MF428x, MF429x only)/PDF (Digital signature)³ (MF428x, MF429x only)

Max. scan width Scan to E-mail / PC / USB memory key / FTP

TIFF/JPEG/PDF/PNG4 ITU-T 37 iFAX

FΔX MF426dw. MF429x only INTERFACE & SOFTWARE Interface type

Double sided printing

Operating System compatibility

Network Protocol

USB 2.0 Hi-Speed, 10BASE-T/100BASE-TX/1000Base-T, Wireless 802:1lb/g/n, Wireless Direct Connection Windows* 10 / Windows* 8.1 / Windows* 7 / Server* 2016 / Server* 2012R2 / Server* 2012 / Server* 2008R2 / Server* 2008 Mac OS X version 10.8.5 & up

Print: LPD, RAW, Port9100, IPP, IPPS, WSD (IPv4,IPv6) Scan; Email, SMB, WSD-Scan(IPv4, IPv6), FTP-Scan, iFAX

TCP/IP Application Services: Bonjour(mDNS), HTTP, HTTPS, POP before SMTP (IPv4,IPv6) DHCP, ARP+PING, Auto IP, WINS (IPv4) DHCPV6 (IPv6)

Management: SNMPv1, SNMPv3 (IPv4,IPv6)

Security (wired): IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS)

Security (wireless): WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(AES)



TECHNICAL SPECIFICATIONS

i-SENSYS MF421dw \ MF426dw \ MF428x \ MF429x

Software and printer management

MF Scan Utility,
Remote User Interface (RUI),
Department ID Management,
Toner Status Tool,
IW Management Console: Server-based software for
centralised management of a fleet of devices
eMaintenance: embedded RDS allows remote
eMaintenance services such as meter capture, automatic
consumables management and remote diagnostics.
Universal Log-in Manager (MF428x, MF429x only)
uniFLOW online (MF428x, MF429x only)
uniFLOW compatibility with embedded uniFLOW Login
Device Client (MF428x, MF429x only)

CONSUMABLES

Cartridges

Accessories/ options

Cartridge 052 (3,100 pages ¹⁰)¹¹ Cartridge 052H (9,200 pages ¹⁰)¹¹

CST.Feeding Module-AH1 (550-sheet cassette)
TEL 6 Kit Long Cord (Telephone handset)
(MF426dw, MF429x only)
Barcode Printing Kit-ElE (MF428x, MF429x only)
MiCard Multi (Card reader for identification with RFID or
magnetic cards with uniFLOW) (MF428x, MF429x only)
Micard Plus (Card reader for identification with RFID or
magnetic cards with uniFLOW) (MF428x, MF429x only)
MiCard Attachment Kit-B1 (MF428x, MF429x only)
Send PDF Security Feature Set-E1 (MF428x, MF429x only)

GENERAL FEATURES

Recommended Monthly Print Volume

Duty cycle Processor Speed Memory

Control panel Dimensions with trays (W x D x H)

Installation space (W x D x H) Weight

Operating environment

Power Source

Power Consumption

750 - 4,000 pages per month

Max. 80,000 pages per month⁷

800MHz x 2 1GB

12.7 cm LCD Colour Touch Screen 453 mm x 464 mm x 392 mm

682 mm x 1.083 mm x 895 mm

Approx. 16.9 Kg

Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80% RH (no condensation) 220-240V(±10%) 50/60Hz (±2Hz)

Maximum: Approx. 1,300 W Standby: Approx. 10 W Sleep mode: Approx. 0.9 W Typical Electricity Consumption (TEC): 1.2 kWh/week (230V) For detailed information relating to Lot26 regulation,

please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx

Sound Pressure⁸ : Active: 55 dB Standby: Inaudible⁹ Sound Power⁸: Active: 72.2 dB Standby: Inaudible⁶

Notes:

 $^{
m II}$ A Canon PCL5e driver is not supplied, however PCL5e commands are supported on the device.

^[2] Accessory - Barcode Printing Kit-E1E - is required

[3] Accessory - Send PDF Security Feature Set-E1 is required

[4] Scan by MF Scan Utility or Canon PRINT Business app

[5] Based on ITU-T Standard Chart No. 1

^[6]Linux support both printing and scanning Available from December 2018.

^[7] Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product

[8] Declared noise emission in accordance with ISO 9296

[9] Inaudible means that the emission sound pressure level for a bystander is lower than absolute standard for background noise in accordance with ISO 7779

[10] Based on ISO/IEC 19752

[11] Printer ships with Cartridge 052 (3,100 pages)



Canon Inc.

Canon Europe

canon-europe.com **English** edition © Canon Europa N.V.,2018

RELIABLE, SECURE AND EASY-TO-USE MULTI-FUNCTION PRINTER FOR AN OFFICE OR SME.

The i-SENSYS MF420 series is a multi-function printer offering SMEs speed, durability, and quality. Mobile connectivity maximises productivity.

Sales Start Date: April 2018

i-SENSYS MF421dw \ MF426dw \ MF428x \ MF429x



PRODUCT DETAILS:

Product Name	Mercury Code	EAN Code
i-SENSYS MF421dw	2222C008AA	4549292090413
i-SENSYS MF426dw	2222C007AA	4549292090406
i-SENSYS MF428x	2222C006AA	4549292090390
i-SENSYS MF429x	2222C005AA	4549292090383

ACCESSORIES:

Mercury Code	EAN Code
0732A033AA	4549292092769
5146B002AA	4549292027235
5143B002AA	N/A (e-delivery)
9594B002AA	N/A (e-delivery)
0752A054AA	4960999453910
0752A053AA	4960999453897
0752A055AA	4960999453927
	0732A033AA 5146B002AA 5143B002AA 9594B002AA 0752A054AA 0752A053AA

CONSUMABLES:

Product Name	Mercury Code	EAN Code
Cartridge 052	2199C002AA	4549292089400
Cartridge 052 H	2200C002AA	4549292089424

EASY SERVICE PLAN:

Product Name	Mercury Code	EAN Code
Installation service	7950A546AA	4960999794426
3-year on-site next day service-Pack C (MF426dw & MF429x)	7950A527AA	4960999793313
3-year on-site next day service-Pack B (MF421dw & MF428x)	7950A526AA	4960999793306

