

Cisco Redundant Power System 2300

The Cisco® Redundant Power System 2300 (Cisco RPS 2300) is a redundant power system that increases availability for converged data, voice, and video networks. The system delivers power supply redundancy and resiliency for a variety of power requirements, including Power over Ethernet (PoE). Providing seamless failover in switches and routers like the Cisco Catalyst 3750-E and the Integrated Services Routers, the Cisco RPS 2300 ensures uninterrupted operation and protection against device power supply failures.

The Cisco RPS 2300 can provide complete internal power supply redundancy for up to two attached networking devices. It has two power supply bays in a 1 rack-unit form factor, and can accept 1150W AC or 750W AC power supply modules. These power supply modules are also used with Cisco Catalyst® 3750-E and 3560-E Series Switches. With two 1150W AC power supplies, the Cisco RPS 2300 is capable of fully backing up two 48-port switches delivering 15.4W of PoE on all ports. The Cisco RPS 2300 also has a replaceable fan module.

The Cisco RPS 2300 helps ensure uninterrupted operation of the connected device in the event of power supply failure. Additionally, if the power supply of the attached Cisco Catalyst 3750-E or 3560-E Series Switch resumes operation, the Cisco RPS 2300 will back off with no interruption to the switch's power.

The Cisco RPS 2300 can be combined with the Cisco Catalyst 3750-E and 3560-E PoE switches and uninterruptible power supply (UPS) systems to provide a resilient, highly available converged network, offering protection against:

- Internal power supply failures in network devices
- Failure of an AC circuit (a circuit breaker tripping, for example)
- Interruption of utility power

The Cisco RPS 2300 supports Cisco router and fixed switches, including:

- Cisco Catalyst 3750-E Series Switches
- Cisco Catalyst 3750 Series Switches
- Cisco Catalyst 3560-E Series Switches
- Cisco Catalyst 3560 Series Switches
- Cisco Catalyst 3550 Series Switches
- Cisco Catalyst 2960 Series Switches
- Cisco Catalyst 2950 Series Switches
- Cisco Catalyst Express 500 Series Switches (select PoE models only)
- Cisco 3825 Integrated Services Routers
- Cisco 2851 Integrated Services Routers
- Cisco 2821 Integrated Services Routers
- Cisco 2811 Integrated Services Routers

NEW FEATURES

The new features introduced by the Cisco RPS 2300 are:

- Greater ease of use
 - Failover to Cisco RPS 2300 when switch power supply fails
 - Automatic back-off when the switch power supply resumes operation
 - Intelligent power management (through Cisco Catalyst 3750-E and 3560-E Series Switches)
 - Cisco RPS 2300 and switch can have separate AC sources
- Greater modularity
 - Uses the same 1150W and 750W power supplies as the Cisco Catalyst 3750-E and 3560-E Series Switches
 - Replaceable fan module
 - More devices supported
 - Supports a wide variety of Cisco Catalyst switches and Cisco integrated services routers
 - With six RPS connectors, up to two switches can be actively backed up

AVAILABILITY

The Cisco RPS 2300 will be available in December 2006.

ORDERING INFORMATION

- Model number PWR-RPS2300 includes the following:
 - Cisco RPS 2300 (PWR-RPS2300)
 - 1 RPS cable. Users may order either the CAB-RPS2300-E= compatible with Cisco Catalyst 3750-E and 3560-E Series Switches or the CAB-RPS2300= compatible with all other network devices. Extra cables must be ordered separately or as spares.
 - At least 1 power supply, either C3K-PWR-1150WAC to back up 48 ports of full PoE or C3K-PWR-750WAC for 24 ports of full PoE with 1 power cable for every power supply ordered
 - 1 fan module (BLWR-RPS2300=)
 - 1 power supply bay insert (BLNK-RPS2300=) to block a power supply bay for effective cooling in the Cisco RPS 2300. Note: This insert will only be provided when ordering an RPS 2300 with just one power supply. It will need to be ordered as a spare while ordering an RPS 2300 with two power supplies.
 - 1 Cisco RPS 2300 accessory kit (ACC-RPS2300=)

- Orderable spares include:

Model Number	Product Description
PWR-RPS2300	RPS 2300 chassis
C3K-PWR-1150WAC	Catalyst 3750-E/3560-E 1150WAC power supply
C3K-PWR-750WAC	Catalyst 3750-E/3560-E 750WAC power supply
BLWR-RPS2300=	Spare 45CFM Blower for Cisco Redundant Power System 2300
CAB-RPS2300-E=	Spare RPS Cable RPS 2300 Cat 3750E/3560E Switches
CAB-RPS2300=	Spare RPS Cable for Cisco Redundant Power System 2300
BLNK-RPS2300=	Spare Bay Insert for Cisco Redundant Power System 2300
ACC-RPS2300=	Spare Accessory Kit for Cisco Redundant Power System 2300

SERVICE AND SUPPORT

Cisco SMARTnet[®] maintenance contracts are available for the Cisco RPS 2300:

Model Number	Product Description
CON-SNT-RPS2300	SMARTnet 8x5xNext Business Day Advance Replacement Service
CON-SNTE-RPS2300	SMARTnet 8x5x4hr Advance Replacement Service
CON-SNTP-RPS2300	SMARTnet 24x7x4hr Advance Replacement Service
CON-S2P-RPS2300	SMARTnet 24x7x2hr Advance Replacement Service
CON-OS-RPS2300	SMARTnet 8x5xNext Business Day Onsite Replacement Service
CON-OSE-RPS2300	SMARTnet 8x5x4hr Onsite Replacement Service
CON-OSP-RPS2300	SMARTnet 24x7x4hr Onsite Replacement Service
CON-PREM-RPS2300	SMARTnet 24x7x2hr Onsite Replacement Service

For more information about Cisco service offerings, visit:

http://www.cisco.com/en/US/products/ps6897/serv_group_home.html

FOR MORE INFORMATION

For more information about the Cisco RPS 2300, visit:

<http://www.cisco.com/en/US/products/ps7130/index.html>



Americas Headquarters
Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883

Asia Pacific Headquarters
Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Europe Headquarters
Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: +31 0 800 020 0791
Fax: +31 0 20 357 1100

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

©2006 Cisco Systems, Inc. All rights reserved. CCVP, the Cisco logo, and the Cisco Square Bridge logo are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn is a service mark of Cisco Systems, Inc.; and Access Registrar, Aironet, BPX, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Enterprise/Solver, EtherChannel, EtherFast, EtherSwitch, Fast Step, Follow Me Browsing, FormShare, GigaDrive, GigaStack, HomeLink, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, iQuick Study, LightStream, Linksys, MeetingPlace, MGX, Networking Academy, Network Registrar, Packet, PIX, ProConnect, RateMUX, ScriptShare, SlideCast, SMARTnet, StackWise, The Fastest Way to Increase Your Internet Quotient, and TransPath are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0609R)