Zebra® GX420™/GX430™ Desktop Printers

Best-in-Class Desktop Thermal Printers

G-Series™ GX420/GX430: Always a Perfect Fit

Best-in-class G-Series GX™ printers offer the widest range of features of any desktop thermal printer, so they're a perfect fit for a wide variety of industries and applications. Sleek, compact, and durable, they bring top speed and performance to 4-inch-wide label, tag or receipt printing.

An Easy Fit

The easy-to-use design provides simple, fast media loading and, when you choose the GX420t™ or the GX430t™ direct thermal/thermal transfer versions, the easiest ribbon-loading on the market. And with the smallest footprint in a 4-inch desktop printer, the direct thermal GX420d™ fits neatly into your most congested workspaces.

With options that increase your media flexibility, like adjustable sensor, cutter and peeler, the GX model fits diverse applications. And the GX430t, with clear 300-dpi resolution, is ideal for 2-D bar codes, fine text and complex graphics.

Accelerate Your Printing Productivity

At 6 inches per second, the GX offers the best in-class speed on the market to meet your low- to medium-volume printing applications. And with its 32-bit processor, it increases your productivity with faster "first label out" and no between-label delay.

Easy to Integrate and Manage

- With both Zebra programming languages on board, GX models fit both into legacy EPL™ desktop printer environments and with Zebra ZPL® tabletop and mobile printers.

- With USB/serial/parallel connectivity, GX models easily integrate into existing systems. For increased network throughput, choose the 10/100 Ethernet option. Or for wireless freedom, connect with the 802.11b/g or Bluetooth® options.

- If you're an IT manager, you'll appreciate remote printer management and host status reporting features that simplify administrators' jobs and reduce printer downtime.

Well-suited for any industry and a variety of applications, reliable GX models are a smart investment, and always a perfect fit.

Quick Specs*

STANDARD FEATURES

EPL and ZPL co-resident on all models

5"/127 mm (outside diameter) media capacity

Quick and easy ribbon loading

Smallest footprint in class

Head-up sensor

PRINTER SPECIFICATIONS

Print Speed

6"/152 mm per second (maximum)

Print Width

4.09"/104 mm

Print Length

39"/991 mm

Print Method

Direct thermal or thermal transfer

Resolution

203 dpi/8 dots per mm

300 dpi/12 dots per mm (Only on GX430t)

Memory

8 MB SDRAM; 4MB Flash

8 MB (12 MB total) Flash with real-time clock (optional)

Connectivity

Serial, USB and parallel standard

10/100 Ethernet (optional)

802.11b/g wireless (optional)

Bluetooth wireless (optional)

Wireless options include LCD for visual communication

www.zebra.com/g-series